



DATA SHEET – MwStop® CHECK VALVE

Technical Data - Standard-Housing

Article no.	Mw181-45-3std	soft-membrane	
	Mw181-55-3std	std-membrane	
	Mw181-65-3std	hard-membrane	
DN	200		
Diameter	181		
Length	400 mm		
Range of application	Ø 182 - 199 mm		
Material case	EN 1.4404/ASIS 316		
Material membrane	EPDM		
Material fastening bracket	EN 1.4404/ASIS 316		
	soft-membrane	std-membrane	hard-membrane
max. backflow pressure	3 m H ₂ O (0,3bar)	5 m H ₂ O (0,5bar)	8 m H ₂ O (0,8bar)
Horizontal opening pressure	234 mm H ₂ O	304 mm H ₂ O	339 mm H ₂ O
Horizontal closing pressure	104 mm H ₂ O	139 mm H ₂ O	154 mm H ₂ O
max. flow velocity	2 m/s	Fitting for higher flow velocity on request	

Membranes are hydrogen sulfide (H₂S) resistant

General distribution: MTA Messtechnik GmbH

A - 9300 St. Veit an der Glan, Handelsstr. 14 - 16 | www.mta-messtechnik.at | office@mta-messtechnik.at | T +43 4212 71491

Place of jurisdiction: A - 9300 St. Veit an der Glan, FN 226770 k Company register Klagenfurt,

The current terms and conditions can be found on our website: www.mta-messtechnik.at

Produced by: MTA-Water Products GmbH