



DATA SHEET – MwStop® CHECK VALVE

Technical Data - Short-Housing

Article no.	Mw240-45-3sh	soft-membrane	
	Mw240-55-3sh	std-membrane	
	Mw240-65-3sh	hard-membrane	
DN	250		
Diameter	240		
Length	350 mm		
Range of application	Ø 237* - 258 mm (with outer sealing) *) Minimum installation dimension with suitable sealing tape (without outer sealing): min. Ø 233mm		
Material case	EN 1.4404/ASIS 316		
Material membrane	EPDM		
Material fastening bracket	EN 1.4404/ASIS 316		
max. backflow pressure	soft-membrane 2 m H ₂ O (0,2bar)	std-membrane 3 m H ₂ O (0,3bar)	hard-membrane 3 m H ₂ O (0,3bar)
Horizontal opening pressure	159 mm H ₂ O	174 mm H ₂ O	194 mm H ₂ O
Horizontal closing pressure	89 mm H ₂ O	109 mm H ₂ O	119 mm H ₂ O
max. flow velocity	2 m/s Fitting for higher flow velocity on request		

Membranes are hydrogen sulfide (H₂S) resistant

General distribution: MTA Messtechnik GmbH

A - 9300 St. Veit an der Glan, Handelsstr. 14 - 16 | www.mta-messtechnik.at | office@mta-messtechnik.at | T +43 4212 71491

Place of jurisdiction: A - 9300 St. Veit an der Glan, FN 226770 k Company register Klagenfurt,

The current terms and conditions can be found on our website: www.mta-messtechnik.at

Produced by: MTA-Water Products GmbH