



# DATA SHEET – MwStop® CHECK VALVE

## Technical Data – One collar

<b>Article no.</b>	Mw440-45-3oc	soft-membrane	
	Mw440-55-3oc	std-membrane	
	Mw440-65-3oc	hard-membrane	
<b>DN</b>	450		
<b>Diameter</b>	443		
<b>Length</b>	813.20 mm		
<b>Range of application</b>	Ø 435* - 465 mm (with outer sealing) *) Minimum installation dimension with suitable sealing tape (without outer sealing): <b>min. Ø 432 mm</b>		
<b>Material case</b>	EN 1.4404/ASIS 316		
<b>Material membrane</b>	EPDM		
<b>Material fastening bracket</b>	EN 1.4404/ASIS 316		
	<b>soft-membrane</b>	<b>std-membrane</b>	<b>hard-membrane</b>
<b>max. backflow pressure</b>	3 m H <sub>2</sub> O (0,3bar)	5 m H <sub>2</sub> O (0,5bar)	8 m H <sub>2</sub> O (0,8bar)
<b>Horizontal opening pressure</b>	199 mm H <sub>2</sub> O	219 mm H <sub>2</sub> O	249 mm H <sub>2</sub> O
<b>Horizontal closing pressure</b>	124 mm H <sub>2</sub> O	144 mm H <sub>2</sub> O	164 mm H <sub>2</sub> O
<b>max. flow velocity</b>	3 m/s Fitting for higher flow velocity on request		

Membranes are hydrogen sulfide (H<sub>2</sub>S) resistant

### General distribution: MTA Messtechnik GmbH

A - 9300 St. Veit an der Glan, Handelsstr. 14 - 16 | www.mta-messtechnik.at | office@mta-messtechnik.at | T +43 4212 71491

Place of jurisdiction: A - 9300 St. Veit an der Glan, FN 226770 k Company register Klagenfurt,

The current terms and conditions can be found on our website: www.mta-messtechnik.at

Produced by: MTA-Water Products GmbH