



DATA SHEET – MwStop® CHECK VALVE

Technical Data - Short-Housing

Article no.	Mw290-45-3sh	soft-membrane	
	Mw290-55-3sh	std-membrane	
	Mw290-65-3sh	hard-membrane	
DN	300		
Diameter	290		
Length	400 mm		
Range of application	Ø 285* - 308 mm (with outer sealing) *) Minimum installation dimension with suitable sealing tape (without outer sealing): min. Ø 281 mm		
Material case	EN 1.4404/ASIS 316		
Material membrane	EPDM		
Material fastening bracket	EN 1.4404/ASIS 316		
max. backflow pressure	soft-membrane	std-membrane	hard-membrane
Horizontal opening pressure	2 m H ₂ O (0,3bar)	3 m H ₂ O (0,3bar)	3 m H ₂ O (0,3bar)
Horizontal closing pressure	184 mm H ₂ O	214 mm H ₂ O	239 mm H ₂ O
	134 mm H ₂ O	164 mm H ₂ O	179 mm H ₂ O
max. flow velocity	3 m/s Fitting for higher flow velocity on request		

Membranes are hydrogen sulfide (H₂S) resistant

General distribution: MTA Messtechnik GmbH

A - 9300 St. Veit an der Glan, Handelsstr. 14 - 16 | www.mta-messtechnik.at | office@mta-messtechnik.at | T +43 4212 71491

Place of jurisdiction: A - 9300 St. Veit an der Glan, FN 226770 k Company register Klagenfurt,

The current terms and conditions can be found on our website: www.mta-messtechnik.at

Produced by: MTA-Water Products GmbH