



DATA SHEET – MwStop® CHECK VALVE

Technical Data - Standard-Housing

Article no.	Mw490-45-3std	soft-membrane	
	Mw490-55-3std	std-membrane	
	Mw490-65-3std	hard-membrane	
DN	500		
Diameter	490		
Length	970 mm		
Range of application	Ø 491 - 504 mm		
Material case	EN 1.4404/AISI 316L		
Material membrane	EPDM		
Material fastening bracket	EN 1.4404/AISI 316L		
max. backflow pressure	soft-membrane	std-membrane	hard-membrane
	3 m H ₂ O (0,3bar)	5 m H ₂ O (0,5bar)	8 m H ₂ O (0,8bar)
Horizontal opening pressure	259 mm H ₂ O	274 mm H ₂ O	309 mm H ₂ O
Horizontal closing pressure	174 mm H ₂ O	184 mm H ₂ O	209 mm H ₂ O
max. flow velocity	4 m/s		
	Fitting for higher flow velocity on request		

Membranes are hydrogen sulfide (H₂S) resistant


General distribution: MTA Messtechnik GmbH

A - 9300 St. Veit an der Glan, Handelsstr. 14 - 16 | www.mta-messtechnik.at | office@mta-messtechnik.at | T +43 4212 71491

Place of jurisdiction: A - 9300 St. Veit an der Glan, FN 226770 k Company register Klagenfurt,

The current terms and conditions can be found on our website: www.mta-messtechnik.at

Produced by: MTA-Water Products GmbH



MTA		Maßstab 1:5	
Wateproducts GmbH		Projekt: MwStop	
Name		DN500 Assembly	
Datum		Baugruppe: DN500 Assembly	
Version		1	
Erstellt		A2	
Geprüft			
Freigegeben			
Material		08 AlMg 1.1.1.045	
Gewicht		-	
Bauteil		Bauteil	
Größe		Größe	
Anzahl		Anzahl	

Diese Zeichnung kann nur durch den Hersteller und/oder den Auftraggeber für die Verwendung der Bauteile im Rahmen der Vertragsbedingungen und/oder der technischen Zeichnungen verwendet werden. Jede Weitergabe oder Nutzung ohne schriftliche Genehmigung ist ausdrücklich untersagt. Die Haftung für die Richtigkeit der Zeichnung liegt ausschließlich beim Auftraggeber.