



DATA SHEET – MwStop® CHECK VALVE

Technical Data – One collar

Article no.	Mw985-45-3oc	soft-membrane	
	Mw985-55-3oc	std-membrane	
	Mw985-65-3oc	hard-membrane	
DN	1000		
Diameter	985		
Length	1774.20 mm		
Range of application	Ø 981* - 1008 mm (with outer sealing) *) Minimum installation dimension with suitable sealing tape (without outer sealing): min. Ø 976 mm		
Material case	EN 1.4404/AISI 316L		
Material membrane	EPDM		
Material fastening bracket	EN 1.4404/AISI 316L		
	soft-membrane	std-membrane	hard-membrane
max. backflow pressure	3 m H ₂ O (0,3bar)	5 m H ₂ O (0,5bar)	8 m H ₂ O (0,8bar)
Horizontal opening pressure	329 mm H ₂ O	379 mm H ₂ O	424 mm H ₂ O
Horizontal closing pressure	219 mm H ₂ O	249 mm H ₂ O	279 mm H ₂ O
max. flow velocity	4 m/s		
	Fitting for higher flow velocity on request		

Membranes are hydrogen sulfide (H₂S) resistant

General distribution: MTA Messtechnik GmbH

A - 9300 St. Veit an der Glan, Handelsstr. 14 - 16 | www.mta-messtechnik.at | office@mta-messtechnik.at | T +43 4212 71491

Place of jurisdiction: A - 9300 St. Veit an der Glan, FN 226770 k Company register Klagenfurt,

The current terms and conditions can be found on our website: www.mta-messtechnik.at

Produced by: MTA-Water Products GmbH

